Triton MANIX Specifications

	Manix ST-50 Euro 4	Manix ST-125 Euro 4
ENGINE TYPE	Single Cylinder, 4 Stroke, Air- Cooled, 2 Valve	Single Cylinder, 4 Stroke, Air- Cooled, 2 Valve
ENGINE	•	·
BORE/STROKE mm DISPLACEMENT ml COMPRESSION RATIO MAXIMUM POWER KW/(r/min) MAXIMUM TORQUE Nm/(r/min) MAXIMUM SPEED (MPH) FUEL CONSUMPTION (Urban) MPG MINIMUM UNLOADED STABLE SPEED r/min IGNITION TYPE STARTER SYSTEM LUBRICATION SYSTEM EFI TYPE OBD INTERFACE CLUTCH TRANSMISSION SPARK PLUG	39.0 x 41.4 49 8.8:1 0.92/5400 1.85/3200 30 185 1400+/-100 ECU Electric & Kick Start Pressure and Splash Single point + Closed loop control 16-pin Wet multiple plate/ Manual 4 Speed NGK/CR6HSA	52.4 x 67 124 9.5:1 6.2/7500 9.2/4500 55 133 1400+/-100 ECU Electric & Kick Start Pressure and Splash Single point + Closed loop control 16-pin Wet multiple plate/ Manual 4 Speed NGK/CR6HSA
CHASSIS RIM RIM SIZE F&R FRONT TYRE REAR TYRE BRAKE SYSTEM FRONT SUSPENSION REAR SUSPENSION FUEL LEVEL GAUGE	10 inch Steel F: 2.5 x 10 / R: 2.5 x 10 3.5-10 / 90/90-10 3.5-10 / 90/90-10 Front Disc / Rear Drum Telescopic Forks Spring / Oil Magnetic induction	10 inch Mag alloy F: 2.5 x 10 / R: 2.5 x 10 3.5-10 / 90/90-10 3.5-10 / 90/90-10 Front and Rear Disc (CBS) Telescopic Forks Spring / Oil Magnetic induction
DIMENSIONS LEGNTH mm WIDTH mm HEIGHT mm WHEELBASE mm MIN GROUND CLEARANCE mm HANDLEBAR HEIGHT mm SEAT HEIGHT mm NET WEIGHT kg FUEL TANK CAPACITY Ltr	1500 / 1640 (Rack) 660 965 1060 130 950 800 / 850 81	1500 / 1640 (Rack) 660 965 1060 130 950 800 / 850 84 5.5
PRICE - Note: On the road fees have not been included	£3,200	£3,500

Numbered Limited Edition Versions Starts from an additional £1,000 Please call for full build details and availability